

## FABRIC REGENERATOR PASTE No. 8

### AGGRESSIVE INK HAZE AND STENCIL RESIDUE REMOVER

**Fabric Regenerator Paste No. 8** removes diazo stains; pigment stains from stencil materials; ink stains from dyes, pigments, or resins; and virtually all types of dried ink dried emulsion, and stencil scum (emulsion residue resulting from incomplete decoating). It is used together with the ink solvent, and must be used with a high pressure, commercial power spray. **Fabric Regenerator Paste No. 8** is recommended for use with all stencil systems on all types of fabric (except metalized polyester). **Fabric Regenerator Paste No. 8** is intended for industrial use only and should be used under conditions of adequate ventilation. Workers should wear protective gloves, goggles, and plastic or rubber aprons.

#### INSTRUCTIONS

##### **Step 1: REMOVE THE STENCIL BEFORE USING FABRIC REGENERATOR PASTE NO. 8**

Remove direct emulsion, capillary film, and direct/indirect stencils with **Stencil Remover Liquid No. 4**, **Stencil Remover Paste No. 5**, or diluted Ulano Chemical Line Concentrates, **Stencil Remover Liquid Concentrate No. 42** or **Stencil Remover Power No. 44**.

##### **Step 2: DRY THE SCREEN**

After rinsing off the stencil and stencil remover, allow the screen to dry.

##### **Step 3: APPLY INK SOLVENT AND FABRIC REGENERATOR PASTE NO. 8**

Work under adequate ventilation. Wear protective gloves, goggles, and a plastic or rubber apron.

Method 1: Wet the screen with the ink solvent recommended by the ink manufacturer. Brush **Fabric Regenerator Paste No. 8** on both sides of the screen with a medium-stiff nylon bristle brush.

Method 2: Mix equal parts of the ink solvent and **Fabric Regenerator Paste No. 8**, then brush the mixture on both sides of the screen with a medium-stiff nylon bristle brush.

##### **Step 4: WAIT 10 – 15 MINUTES**

Let the screen stand for 10 – 15 minutes to allow the solvent and **Fabric Regenerator Paste No. 8** to react with the ink haze and stencil residue.

##### **Step 5: RINSE, THEN USE A COMMERCIAL POWER SPRAY**

Again, be sure to wear protective gloves, goggles and a plastic or rubber apron.

Flush the screen with a gentle spray of water to remove **Fabric Regenerator Paste No. 8** and screen residues without risk of harmful "splash-backs" to the eyes or skin.

Spray the screen with a high-pressure commercial power spray.

Repeat the treatment if necessary.

#### Caution

**Fabric Regenerator Paste No. 8** is corrosive and caustic, and will cause severe burns on contact. Avoid contact with the skin, eyes, mucous membranes, and clothing. Harmful or fatal if swallowed. Flush spills immediately with water mixed with equal parts of vinegar. First aid: Eyes—flush immediately with water at least 20 minutes. External—flood with water for at least 15 minutes; then wash the exposed area with a solution of equal parts of vinegar and water. Internal—drink large quantities of water or milk followed by citrus juice or diluted vinegar; do not induce vomiting. Call a physician at once.